

Model		Eiq-CRFC18K-V3 IN	
Indoor power supply		V/Ph/Hz	220~240/1/50
Cooling	Capacity	KW	2.0-5.6
	Power input	W	420-2100
	Current input	A	2.1-10.1
	EER	W/W	3.33
	SEER	W/W	6.1
Heating	Capacity	KW	2.5-6.0
	Input	W	500-1940
	Rated current	A	2.5-9.2
	COP	W/W	4.12
	SCOP	W/W	4.0
Energy rate		Cooling	A++
Energy rate		Heating	A+
Max. power input		W	2400
Max. current input		A	11.4
Indoor fan motor	Model		
	Brand		
	Power output	W	35
	Capacitor	μF	-
	Speed	r/min	790
	Insulation class		E
Indoor coil	Number of rows		2
	Tube pitch(a)xrow pitch(b)	mm	21×13.37
	Fin spacing	mm	1.4
	Fin type		Hydrophilic
	Tube outside dia. and type	mm	Φ7 inner grooved
	Coil lengthxheightxwidth	mm	1317x210x26.74
	Number of circuits		4
Indoor air flow(High speed)		m ³ /h	650
Indoor noise level	power level	dB(A)	46-55
	pressure level		36/39/43
Indoor unit	Dimension(W*H*D)	Body(mm)	565x267x565
		Panel(mm)	650x29.8x650
	Packing(W*H*D)	Body(mm)	745x375x675
		Panel(mm)	750x95x750
	Net/Gross weight	Body(Kg)	16.5/21.5
		Panel(Kg)	2.7/4.0
Max pressure		MPa	4.2
Refrigerant type			R410A
Refrigerant piping	Liquid side/Gas side	mm	Φ6.35/Φ12.7
Drainage pipe		mm	DN25
Standard controller			
Operation temp		°C	16~32
Ambient temp	cooling	°C	-5~50
	heating	°C	-15~30
Application area		m ²	20-35