

Model		Eiq-SSRFC24K-V3 IN	
Indoor power supply		V/Ph/Hz	220~240/1/50
Cooling	Capacity	KW	3.5-7.0-8.0
	Power input	W	600-2150-3000
	Current input	A	2.5-9.8-13
	EER	W/W	3.26
	SEER	W/W	5.6
Heating	Capacity	KW	4.5-7.7-8.5
	Input	W	1500-2075-2600
	Rated current	A	5.5-9.5-11
	COP	W/W	3.72
	SCOP	W/W	4.0
Energy rate		Cooling	A+
Energy rate		Heating	A+
Max. power input		W	3200
Max. current input		A	14
Indoor fan motor	Model		
	Brand		
	Power output	W	60
	Capacitor	μF	-
	Speed	r/min	850/790/600
	Insulation class		E
Indoor coil	Number of rows		2
	Tube pitch(a)xrow pitch(b)	mm	21×13.37
	Fin spacing	mm	1.45
	Fin type		Hydrophilic
	Tube outside dia. and type	mm	Φ7 inner grooved
	Coil lengthxheightxwidth	mm	2000×168×26.74
	Number of circuits		8
Indoor air flow(High speed)		m ³ /h	1100/1000/850
Indoor noise level	power level	dB(A)	56~63
	pressure level		43/46/49
Indoor unit	Dimension(W*H*D)	Body(mm)	840×230×840
		Panel(mm)	950×50×950
	Packing(W*H*D)	Body(mm)	920×265×920
		Panel(mm)	1030×105×1030
	Net/Gross weight	Body(Kg)	25/30
		Panel(Kg)	5.4/8.0
Max pressure		MPa	3.8
Refrigerant type			R410A
Refrigerant piping	Liquid side/Gas side	mm	Φ9.52/Φ15.88
Drainage pipe		mm	DN25
Standard controller			
Operation temp		°C	16~32
Ambient temp	cooling	°C	-5~50
	heating	°C	-15~30
Application area		m ²	28-50