

Model			Eiq-SSRFC36K-V3 IN
Indoor power supply		V/Ph/Hz	220~240/1/50
Cooling	Capacity	KW	6.6-10.5-12.8
	Power input	W	740-3275-4600
	Current input	A	2.8-13.6-24.8
	EER	W/W	3.21
	SEER	W/W	5.1
Heating	Capacity	KW	7.35-11.5-13.2
	Input	W	1100-3200-4150
	Rated current	A	4.2-14.7-21.4
	COP	W/W	3.59
	SCOP	W/W	4.0
Energy rate		Cooling	A
Energy rate		Heating	A+
Max. power input		W	4800
Max. current input		A	26
Indoor fan motor	Model		
	Brand		
	Power output	W	100
	Capacitor	μF	-
	Speed	r/min	840/750/650
	Insulation class		E
Indoor coil	Number of rows		2
	Tube pitch(a)xrow pitch(b)	mm	21×13.37
	Fin spacing	mm	1.45
	Fin type		Hydrophilic
	Tube outside dia. and type	mm	Φ7 inner grooved
	Coil lengthxheightxwidth	mm	2000×252×26.74
	Number of circuits		12
Indoor air flow(High speed)		m <sup>3</sup> /h	1800/1700/1550
Indoor noise level	power level	dB(A)	53~61
	pressure level		43/45/48
Indoor unit	Dimension(W*H*D)	Body(mm)	840×285×840
		Panel(mm)	950×50×950
	Packing(W*H*D)	Body(mm)	920×310×920
		Panel(mm)	1030×105×1030
	Net/Gross weight	Body(Kg)	30.5/36
		Panel(Kg)	5.4/8.0
Max pressure		MPa	3.8
Refrigerant type			R410A
Refrigerant piping	Liquid side/Gas side	mm	Φ9.52/Φ15.88
Drainage pipe		mm	DN25
Standard controller			
Operation temp		°C	16~32
Ambient temp	cooling	°C	-5~50
	heating	°C	-15~30
Application area		m <sup>2</sup>	40-70