

| Model | | Eiq-SSRFC60K-V3 IN | |
|-----------------------------|----------------------------|--------------------|---------------------|
| Indoor power supply | | V/Ph/Hz | 220~240/1/50 |
| Cooling | Capacity | KW | 16.0 |
| | Power input | W | 4580 |
| | Current input | A | 10.0 |
| | EER | W/W | 3.50 |
| | SEER | W/W | 5.32 |
| Heating | Capacity | KW | 18.0 |
| | Input | W | 5130 |
| | Rated current | A | 10 |
| | COP | W/W | 3.61 |
| | SCOP | W/W | 3.60 |
| Energy rate | | Cooling | A |
| Energy rate | | Heating | A |
| Max. power input | | W | 6300 |
| Max. current input | | A | 10 |
| Indoor fan motor | Model | | |
| | Brand | | |
| | Power output | W | 75 |
| | Capacitor | μF | 4 |
| | Speed | r/min | 750/650/550 |
| Insulation class | | B | |
| Indoor coil | Number of rows | | 2 |
| | Tube pitch(a)xrow pitch(b) | mm | 21x13.37 |
| | Fin spacing | mm | 1.45 |
| | Fin type | | Hydrophilic |
| | Tube outside dia. and type | mm | Φ7 inner grooved |
| | Coil lengthxheightxwidth | mm | 2000x252x26.74 |
| | Number of circuits | | 12 |
| Indoor air flow(High speed) | | m ³ /h | 1600 |
| Indoor noise level | power level | dB(A) | 46-55 |
| | pressure level | | 37~41 |
| Indoor unit | Dimension(W*H*D) | Body(mm) | 833x286x900 |
| | | Panel(mm) | 950x50x950 |
| | Packing(W*H*D) | Body(mm) | 920x310x985 |
| | | Panel(mm) | 1030x105x1030 |
| | Net/Gross weight | Body(Kg) | 27/32.5 |
| | | Panel(Kg) | 5.4/8 |
| Max pressure | | MPa | 3.8 |
| Refrigerant type | | R410A | |
| Refrigerant piping | Liquid side/Gas side | mm | Φ9.52/Φ15.88 |
| Drainage pipe | | mm | DN25 |
| Standard controller | | | |
| Operation temp | | °C | 16~32 |
| Ambient temp | cooling | °C | -5~50 |
| | heating | °C | -20~30 |
| Application area | | m ² | 64-106 |