

Local single duct air conditioner

ARGO ORION PLUS

398000698



ARGO ORION PLUS is the air conditioner with a contemporary design. The glossy front panel, highlighted by a silver belt, is the result of fashion and interior design contaminations. Thanks to its heat pump, ARGO ORION PLUS is useful all year round.




Pannello comandi digitale con display a LED
Digital control panel with LED display



Flap motorizzato
Auto-opening flap



Cura dei dettagli
Attention to details



Dimensioni
Dimensions



CONTEMPORARY DESIGN AND POWER

- > Top motorized flap with wide automatic swinging, adjustable also by remote control
- > Digital control panel and LED display
- > Multifunctional remote control with LED display
- > Digital programmable ON/OFF timer (24h)
- > Functions: Cooling, Ventilation, Dehumidification and Heating
- > "Swing" function: automatic oscillation or fixed position
- > "Sleep" function: comfort during your sleeping
- > "Memory" function: auto-restart after power failure, keeping last settings
- > "Auto-diagnosis" function, showing errors on display, making it easier troubleshooting
- > "Filter reset" function: the air conditioner indicates when to clean the air filter.
- > 3 speed fan (low, medium, high) + Auto
- > Washable air filter, easy to remove
- > Automatic vaporization of condensate in Cooling mode
- > Possibility of continuous condensate discharge in Dehumidification mode
- > Maximum portability, with practical multi-directional wheels and side handles
- > Exhaust hose, window adapter and kit for fixed window installation included

EAN 8013557618873

/ MODEL		ARGO ORION PLUS	
		Freddo Cooling	Caldo Heating
Potenza max. in freddo (35°C; 80% U.R.) / Max cool. cap. (35°C; 80% R.H.)	BTU/h	13.000	10.000
Potenza nom. in freddo (35°C/24°C) / Rated cool. cap. (35°C/24°C)	kW	3,4	2,7
/ Energy label class		A	A+
EER / RATED EER - COP / RATED COP	kW/kW	2,6	2,80
/ Max Air flowrate (l.-m.-h.)	m³/h	350	
/ Dehumidification	l/24h	30	-
/ Fan speeds	no.	3 + auto	
Sound pressure (l.-m.-h.)	dB(A)	48-50-52	
/ Sound power (h.)	dB(A)	64	
/ Power supply	V/F/Hz	230/1/50	
/ Rated Power input	kW	1,280	0,970
/ Hourly electricity consumption	kWh/60 min	1,3	1,0
/ Thermostat-off mode power consumption	W	nd/na	
/ Standby mode power consumption	W	0,38	
/ Refrigerant type		R290	
/ Refrigerant GWP	kg CO ₂ eq.	3	
/ Refrigerant charge	kg/Tonn CO ₂ eq.	0,21/0,00063	
/ Flexible exhaust tube diameter (inner-outer)	mm	140-150	
/ Flexible exhaust tube (extended lenght)	m	1,5	
/ Net weight	Kg	33,5	
/ Net dimensions (H./W./D.)	mm	710/476/385	