

Model		eiq-CRFC12k	
Average	Pdesignnc	kW	3.5
	SEER	W/W	6.1
	Energy Efficiency Class		A++
	Pdesignnh	kW	3.6
	SCOP	W/W	4.0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
Warmer	Tol	°C	-15
	Pdesignnh	kW	3.6
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
Tbiv	°C	2	
Power supply (Indoor)		V,Hz,Ph	220~240,50,1
Power supply (Outdoor)		V,Hz,Ph	220~240,50,1
Cooling	Capacity	Btu/h	12000(2100-15000)
	Capacity	kW	3.52(0.62-4.40)
	Input	W	960(210-1692)
	Current	A	4.4(1.0-7.7)
Heating	Capacity	Btu/h	14000(2100-17500)
	Capacity	kW	4.10(0.62-5.13)
	Input	W	995(496-1830)
	Current	A	4.5(2.3-8.4)
Indoor fan motor	Model		ZKFP-46-8-1
	Old Model		WZDK46-38G
	Qty		1
	Input	w	45
	Capacitor	uF	---
	Speed(hi/mi/lo)	r/min	700/580/500
Indoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	1360x210x26.74
	g.Number of circuits		4
Indoor air flow		m3/h	650/530/450
Indoor sound pressure level		dB(A)	42/38/34
Indoor sound power level (Hi)		dB(A)	57
Indoor unit	Dimension (W x Dx H)(body)	mm	570x570x260
	Packing (W x Dx H)(body)	mm	655x655x290
	Dimension (W x Dx H)(panel)	mm	647x647x50
	Packing (W x Dx H)(panel)	mm	715x715x123
	Net/Gross weight(body)	kg	16/19
	Net/Gross weight	kg	2.5/4.5
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ25
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ9.52(1/4"/3/8")
Controller		Standard	Remote control
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	0~30