

Model			eiq-CRFC18k
Average	Pdesignc	kW	5.3
	SEER	W/W	6.3
	Energy Efficiency Class		A++
	Pdesignh	kW	4.8
	SCOP	W/W	4.0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
	Tol	°C	-15
Warmer	Pdesignh	kW	5.0
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Power supply (Indoor)		V,Hz,Ph	220~240,50,1
Power supply (Outdoor)		V,Hz,Ph	220~240,50,1
Cooling	Capacity	Btu/h	18000(2700-21000)
	Capacity	kW	5.28(0.79-6.15)
	Input	W	1630(270-2365)
	Current	A	7.5(1.2-10.9)
Heating	Capacity	Btu/h	19000(3000-24000)
	Capacity	kW	5.57(0.88-7.03)
	Input	W	1500(295-2510)
	Current	A	6.8(1.38-11.50)
Indoor fan motor	Model		ZKFP-46-8-1
	Old Model		WZDK46-38G
	Qty		1
	Input	w	45
	Capacitor	uF	---
	Speed(hi/mi/lo)	r/min	750/630/570
Indoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	1360x210x26.74
	g.Number of circuits		4
Indoor air flow		m3/h	660/550/490
Indoor sound pressure level		dB(A)	46/42/38
Indoor sound power level (Hi)		dB(A)	56
Indoor unit	Dimension (W x Dx H)(body)	mm	570x570x260
	Packing (W x Dx H)(body)	mm	655x655x290
	Dimension (W x Dx H)(panel)	mm	647x647x50
	Packing (W x Dx H)(panel)	mm	715x715x123
	Net/Gross weight(body)	kg	16.5/19
	Net/Gross weight	kg	2.5/4.5
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ25
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ12.7(1/4"/1/2")
Controller		Standard	Remote control
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	0~30