

Model		eiq-SSRFC36k	
Power supply		V,Hz,Ph	220~240,50,1
Max. input consumption		W	4500
Max. input current		A	21.0
Compressor	Model		ATF310D43UMT
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	32380
	Input	W	2600
	Rated current(RLA)	A	5.10
	Refrigerant oil	ml	PQE(VG74)/1000
Outdoor fan motor	Model		ZKFN-120-8-2
	Old Model		WZDK120-38G-W
	Qty		1
	Input	W	150
	Capacitor	μF	/
	Speed(Hi)	r/min	950
Outdoor coil	Number of rows		2
	Tube pitch(a)* row pitch(b)	mm	25.4x22
	Fin spacing	mm	1.3
	Fin type		Hydrophilic aluminium
	Tube outside dia.and type	mm	Φ9.52, innergroove tube
	Coil length * height * width	mm	995x762x44
	Number of circuits		4
Outdoor air flow		m3/h	4300
Outdoor sound pressure level		dB(A)	61
Outdoor sound power level		dB(A)	66
Throttle type			Capillary +EXV
Outdoor unit	Dimension(WxDxH)	mm	946x410x810
	Packing(WxDxH)	mm	1090x500x875
	Net/Gross weight	kg	67.2/72.9
Refrigerant	Type		R410A
	GWP		2088
	Charged quantity	Kg	3.2
Design pressure		MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ9.52/Φ15.9(3/8"/5/8")
	Max. pipe length	m	65
	Max. difference in level	m	30
Ambient temperature	Cooling	°C	-15~50
	Heating	°C	-15~24