

Model			eiq-SSRFC36k
Average	Pdesignc	kW	10.5
	SEER	W/W	6.1
	Energy Efficiency Class		A++
	Pdesignh	kW	9.9
	SCOP	W/W	4.0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
	Tol	°C	-15
Warmer	Pdesignh	kW	10.5
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Power supply (Indoor )		V,Hz,Ph	220~240,50,1
Power supply (Outdoor )		V,Hz,Ph	220~240,50,1
Cooling	Capacity	Btu/h	36000(10000-41000)
	Capacity	kW	10.55(2.93-12.02)
	Input	W	4060(975-4620)
	Current	A	18.5(4.2-20.1)
Heating	Capacity	Btu/h	38000(9000-45000)
	Capacity	kW	11.13(2.64-13.19)
	Input	W	3085(880-4690)
	Current	A	13.4(3.8-20.4)
Indoor fan motor	Model		ZKFP-124-8-2
	OldModel		WZDK124-38G
	Qty		1
	Input	w	141
	Capacitor	uF	/
	Speed(hi/mi/lo)	r/min	730/670/600
Indoor coil	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.4
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	2080x210x40.11
	g.Number of circuits		10
Indoor air flow (Hi/Mi/Lo)		m3/h	1900/1750/1460
Indoor sound pressure level (Hi)		dB(A)	53/50/47
Indoor sound power level (Hi)		dB(A)	61
Indoor unit	Dimension (W x Dx H)(body)	mm	840x840x245
	Packing (W x Dx H)(body)	mm	840x840x245
	Dimension (W x Dx H)(panel)	mm	950x950x55
	Packing (W x Dx H)(panel)	mm	1035x1035x90
	Net/Gross weight(body)	kg	25.6/29.6
	Net/Gross weight	kg	5/8
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ32
Refrigerant piping	Liquid side/ Gas side	mm	Φ9.52/Φ15.9(3/8"/5/8")
Controller		Standard	Remote-RG51C/E
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	0~30