

Model			eiq-SSRFC48k
Average	Pdesignnc	kW	14.0
	SEER	W/W	5.6
	Energy Efficiency Class		A+
	Pdesignh	kW	11.5
	SCOP	W/W	4.0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
	Tol	°C	-15
Warmer	Pdesignh	kW	11.8
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Power supply (Indoor)		V,HZ,Ph	220~240,50,1
Power supply (Outdoor)		V,HZ,Ph	220~240,50,1
Cooling	Capacity	Btu/h	47000(13600-55000)
	Capacity	kW	13.78(3.99-16.12)
	Input	W	5159(1330-6200)
	Current	A	23.6(5.8-27.0)
Heating	Capacity	Btu/h	53000(14300-60000)
	Capacity	kW	15.53(4.19-17.59)
	Input	W	4555(1400-6765)
	Current	A	20.8(6.1-29.4)
Indoor fan motor	Model		ZKFP-124-8-2
	OldModel		WZDK124-38G
	Qty		1
	Input	w	141
	Capacitor	uF	---
	Speed(hi/mi/lo)	r/min	780/680/600
Indoor coil	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.4
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	2080x252x40.11
	g.Number of circuits		12
Indoor air flow (Hi/Mi/Lo)		m3/h	1850/1600/1400
Indoor sound pressure level (Hi)		dB(A)	53/49/45
Indoor sound power level (Hi)		dB(A)	63
Indoor unit	Dimension (W x Dx H)(body)	mm	840x840x287
	Packing (W x Dx H)(body)	mm	900x900x292
	Dimension (W x Dx H)(panel)	mm	950x950x55
	Packing (W x Dx H)(panel)	mm	1035x1035x90
	Net/Gross weight(body)	kg	28/32.1
	Net/Gross weight	kg	5/8
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ32
Refrigerant piping	Liquid side/ Gas side	mm	Φ9.52/Φ15.9(3/8"/5/8")
Controller		Standard	Remote control
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	0~30