

Model		eiq-SSRFC60k	
Power supply		V,Hz,Ph	380~415,50,3
Max. input consumption		W	7500
Max. input current		A	14.0
Compressor	Model		ATQ420D1UMU
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	44697
	Input	W	3420
	Rated current(RLA)	A	6.85
	Refrigerant oil	ml	Ester Oil VG74/1400
Outdoor fan motor	Model		ZKFN-85-8-22+ZKFN-85-8-22-2
	Old Model		--
	Qty		1+1
	Input	W	126
	Capacitor	μF	/
	Speed(Hi)	r/min	850
Outdoor coil	Number of rows		2
	Tube pitch(a)* row pitch(b)	mm	25.4x22
	Fin spacing	mm	1.4
	Fin type		Hydrophilic aluminium
	Tube outside dia.and type	mm	Φ9.52,innergroove tube
	Coil length * height * width	mm	990x1270x44
	Number of circuits		8
Outdoor air flow		m3/h	7200
Outdoor sound pressure level		dB(A)	62.5
Outdoor sound power level		dB(A)	75
Throttle type			Capillary +EXV
Outdoor unit	Dimension(WxDxH)	mm	952x415x1333
	Packing(WxDxH)	mm	1095x495x1480
	Net/Gross weight	kg	112.8/126
Refrigerant	Type		R410A
	GWP		2088
	Charged quantity	Kg	4.3
Design pressure		MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ9.52/Φ15.9(3/8"/5/8")
	Max. pipe length	m	65
	Max. difference in level	m	30
Ambient temperature	Cooling	°C	-15~50
	Heating	°C	-15~24