

Model			eiq-SSRFC60k
Average	Pdesignc	kW	16.0
	SEER	W/W	5.6
	Energy Efficiency Class		A+
	Pdesignh	kW	11.5
	SCOP	W/W	4.0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
	Tol	°C	-15
Warmer	Pdesignh	kW	12.2
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Power supply (Indoor)		V,Hz,Ph	220~240,50,1
Power supply (Outdoor)		V,Hz,Ph	380~415,50,3
Cooling	Capacity	Btu/h	55000(17000-63000)
	Capacity	kW	16.12(4.98-18.46)
	Input	W	6395(1660-7100)
	Current	A	11.0(2.9-12.3)
Heating	Capacity	Btu/h	62000(18000-70000)
	Capacity	kW	18.17(5.28-20.51)
	Input	W	5735(1760-7320)
	Current	A	9.9(3.0-12.6)
Indoor fan motor	Model		ZKFN-170-8-1
	OldModel		
	Qty		1
	Input	w	232
	Capacitor	uF	---
	Speed(hi/mi/lo)	r/min	800/680/580
Indoor coil	a.Number of rows		3
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.4
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	965x252x40.11+965x252x40.11
	g.Number of circuits		10
Indoor air flow (Hi/Mi/Lo)		m3/h	1900/1650/1450
Indoor sound pressure level (Hi)		dB(A)	52/49/46
Indoor sound power level (Hi)		dB(A)	68
Indoor unit	Dimension (W x Dx H)(body)	mm	840x840x287
	Packing (W x Dx H)(body)	mm	900x900x292
	Dimension (W x Dx H)(panel)	mm	950x950x55
	Packing (W x Dx H)(panel)	mm	1035x1035x90
	Net/Gross weight(body)	kg	31/34
	Net/Gross weight	kg	5/8
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ32
Refrigerant piping	Liquid side/ Gas side	mm	Φ9.52/Φ15.9(3/8"/5/8")
Controller		Standard	Remote control
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	0~30