

Specification of R410A Inverter Split

Model		INV12T/ INV12TWiFi	
Rated voltage and frequency (Ph-V-Hz)		1Ph/220-240V~/50Hz	
Mode		Cooling	Heating
Rated capacity (W)		3520(1020~3860)	3560(1020~4130)
Cooling power input (W)		1134	975
		(320~1300)	(320~1430)
Heating current input (A)		5.7(1.4 ~ 6.8)	5.3(1.4 ~ 6.3)
SEER/SCOP(W/W)		6.2/A++	4.0/A+
Min. outdoor operating temperature (°C)		-7	
Annual consumption (kW)		198	1015
Liquid side / Gas side (mm/inch)		6.00 (1/4) + 9.52 (3/8)	
Max. refrigerant pipe length		15m	
Max. elevation		5m	
Moisture Removal (L/h)		1.2	
Indoor	Air Flow (m ³ /h)	550	
	Dimensions (L*W*H) (mm)	777x250x205	
	Packaging (L*W*H) (mm)	848x315x275	
	Net / Gross weight (Kg)	8.5/10.5	
	Noise – Sound pressure level (dB/A)	19-40	
	Noise – Sound power level (dB/A)	29-50	
Outdoor	Dimension (L*W*H) (mm)	700x256x552	
	Packaging (L*W*H) (mm)	803-325x600	
	Net / Gross Weight (Kg)	25/28	
	Noise – Sound pressure level (dB/A)	52	
	Noise – Sound power level (dB/A)	60	
	Refrigerant type/weight	R410A/1000g	
	Defrost mode	Automatic defrosting	
	Applicable climate types	T1 (typical -7°C – 43°C)	